

HT-2 Self-ignition Torch With Hose & Auxiliary valve

- For use with MAPP or Propane Gases
- Main Regulator made of brass for safety and reliability
- Dual adjustment switching for safety and convenience



6-blade thruster

50% improved compacted
to 4-blade thruster



Technical Data

Model:	HT-2
Gas Type	MAPP, Propane, LPG
Connection Standard	CGA600
Container	For use with 14.1-16 OZ Containers
Regulator Ratings	2.59MPa (375psi) Maximum Gas Pressure
Copper Tubing Size Capability(With Mapp Gas)	5cm/Soft Solder: Max.Φ2" 2.5cm/Brazing: Max.Φ1"
Max Flame Temperature	>1982°C/3600° F(tested with MAPP gas)
Caution	Low flame setting will result in overheat of the tip
Packing	Carton: 20pcs

HT-3 Hand-held Self-ignition Torch

- Self-Ignition with Aluminum Housing
- 360° Swivel Burn Tip
- High Efficient Turbo Swivel Flame
- Dual gas MAPP or PROPANE
Fits all STANDARD MAPP or PROPANE TANKS 100% Fire Test



Technical Data

Model:	HT-3
Gas Type	MAPP, Propane, LPG
Connection Standard	CGA600
Container	For use with 14.1-16 OZ Containers
Regulator Ratings	2.59MPa (375psi) Maximum Gas Pressure
Copper Tubing Size Capability(With Mapp Gas)	5cm/Soft Solder: Max.Φ2" 2.5cm/Brazing: Max.Φ1"
Max Flame Temperature	>1982°C/3600° F(tested with MAPP gas)
Caution	Low flame setting will result in overheat of the tip
Packing	Carton: 25pcs